

Sentinel Series

Humidifiers

Wine Guardian humidifiers are uniquely designed to deliver superior **performance and reliability**, ensuring the proper conditions for your wine collection and cellar. They use Wine Guardian control system to monitor and control the moisture that needs to be added to the cellar. Available as both integrated or freestanding models.

Integrated Humidifier



Comprehensive

Uses Wine Guardian remote interface for control and readout; a separate controller is not needed. The humidifier is powered directly from the unit so a separate power source is not necessary.

Versatile

Installs on either side of system for application **flexibility**.

Bold

A **sleek and modern** look to compliment any wine cellar design.

Efficient

The redesigned humidifier contains **increased insulation** which prevents sweating even when the unit it is attached to is installed in a humid environment.

Accessible

Quarter-turn fasteners allows for **ease of access** and serviceability. Water hookup is now simpler with the water supply located on the top of the unit.

Strong

Commercial-grade & lightweight design prevents dents and scratches during shipping and installation.

Freestanding Model on Page 2 ▼

Wine Guardian Factory & Headquarters - USA:
7000 Performance Dr, North Syracuse, NY 13212
wineguardian.com | info@wineguardian.com
Designed and Built in the USA

Wine Guardian European Office:
Pestalozzistrasse 2, CH-8201 Schaffhausen,
Switzerland



**Sentinel
Series**

Freestanding Humidifier



Versatile

Can be used with **any** wine cellar cooling system, not just Wine Guardian. Mounting bracket allows for **maximum placement flexibility** including mounted, in-the-racking, or on-the-wall.

Bold

A **sleek and modern** supply grille to compliment any wine cellar design. (Removable)

Strong

Commercial-grade and lightweight design prevents dents and scratches during shipping and installation.

Accessible

Evaporative drip pad system with removable cover and cleanable pad allow for **ease of access** and maintenance. Water hookup is now simpler with the water supply located on the top of the unit.

Efficient

The redesigned humidifier contains **increased insulation** which prevents sweating even when installed in a humid environment.

Humidifier Specifications

Supply Water	Temperature 60°F (16°C) 100°F (38°C)	Capacity 0.42 lbs/hr (0.19 kg/hr) 1.0 lbs/hr (0.45 kg/hr)
Controls	Cellar-mounted remote interface controller	
Power Requirements	Freestanding: Independent Operation: 115 volt, 1 phase, 60 Hz (220/240 volt, 1 phase, 50 Hz) Powered through Wine Guardian: 24 volt (50/60 Hz)	
	Integrated: 24 volt (50/60 Hz)	
Weight	10 lbs (4.5 kg)	

Contact your authorized Wine Guardian distributor for information pertaining to integrated humidification. Manufacturer reserves right, without notice, to make changes to specifications at its sole discretion. Wine Guardian® Through-the-Wall Cooling System US Pat. No. D634760. Wine Guardian® is a registered trademark of Air Innovations®.



Wine Guardian Factory & Headquarters - USA:
7000 Performance Dr, North Syracuse, NY 13212
wineguardian.com | info@wineguardian.com
Designed and Built in the USA

Wine Guardian European Office:
Pestalozzistrasse 2, CH-8201 Schaffhausen,
Switzerland



Sentinel Series